

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



BLACK ALUMINUM

Version: 4
Revision date: 09/11/2017

Page 1 of 9
Print date: 09/11/2017

SECTION 1: IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: BLACK ALUMINUM
Chemical Name: ALUMINUM
Index No: 013-002-00-1
CAS No: 7429-90-5
EC No: 231-072-3

1.2 Relevant identified uses of the substance and uses advised against.

Pyrotechnical compositions

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **ALDEBARÁN SISTEMAS SL**
Address: C/Jerónimo Zurita, 10, entlo izda, 50001
City: Zaragoza
Province: Zaragoza
Telephone: 0034976796134
E-mail: aldebaran@aldebaransistemas.com

1.4 Emergency telephone number: 0034915620420 (Available 24 hours)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance.

In accordance with Regulation (EU) No 1272/2008:

Flam. Sol. 1 : Flammable solid.

Water-react. 2 : In contact with water releases flammable gases.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

Danger

H statements:

H228 Flammable solid.
H261 In contact with water releases flammable gases.

P statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P223 Do not allow contact with water.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



BLACK ALUMINUM

Version: 4
Revision date: 09/11/2017

Page 2 of 9
Print date: 09/11/2017

P231+P232	Handle and store contents under inert gas/.... Protect from moisture.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting/...] equipment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P335+P334	IF ON SKIN: Brush off loose particles from skin. Immerse in cool water [or wrap in wet bandages].
P370+P378	In case of fire: Use dry sand to extinguish.
P402+P404	Store in a dry place. Store in a closed container.
P501	Dispose of contents/container to local/national normative

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Mono-constituent.

Chemical Name:	[1] ALUMINUM
Index No:	013-002-00-1
CAS No:	7429-90-5
EC No:	231-072-3

[1] Substance with a Community workplace exposure limit (see section 8.1).

3.2 Mixtures.

Not Applicable.

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

If wearing contact lenses, remove them. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

No known acute or delayed effects from exposure to the product.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



BLACK ALUMINUM

Version: 4
Revision date: 09/11/2017

Page 3 of 9
Print date: 09/11/2017

SECTION 5: FIREFIGHTING MEASURES.

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Recommended extinguishing methods.

Gently smother burning material with dry sand

Unsuitable extinguishing media

Water

CO₂

Foam

Dry chemical powder

Halogenated hydrocarbon fire extinguisher

5.2 Special hazards arising from the substance.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

The contaminated area should be immediately cleaned with an appropriate de-contaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

Avoid generation of dust clouds

Avoid sources of sparks or other sources of ignition Protect against static electricity

Use proper explosion-proof equipment and spark-proof tools Keep the work area clean

Avoid accidental contact with reactive materials - acids or chemical s - oxidants, etc. Use non-sparking tools

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



BLACK ALUMINUM

Version: 4
Revision date: 09/11/2017

Page 4 of 9
Print date: 09/11/2017

7.2 Conditions for safe storage, including any incompatibilities.

Store in supplied containers until they are used. Keep in a dry room or in a closed store. The area should be properly marked to indicate the presence of a flammable dust. No smoking: there must be a warning.

Avoid sparks or other sources of ignition. Keep the area clean and avoid spills.

Do not store with reactive materials. The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Pyrotechnical mixtures

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
aluminium powder (stabilised)	7429-90-5	United Kingdom [1]	Eight hours		10 (inhalable dust) 10 (inhalable dust) 4 (respirable dust)
			Short term		

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
aluminium powder (stabilised) : 7429-90-5 : 231-072-3	DNEL (Workers)	Inhalation, Long-term, Local effects	3,72 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	Pyrotechnical compositions
Breathing protection:	
PPE:	Particle filter mask
Characteristics:	«CE» marking, category III. Made of filtering material, it covers nose, mouth and chin.
CEN standards:	EN 149
Maintenance:	Check for any tears, defects, etc. before use. Since it is disposable individual protection equipment, it should be replaced after use.
Observations:	Does not protect worker unless properly adjusted. Follow the manufacturer's instructions regarding suitable use of the equipment.
Filter Type needed:	P2
Hand protection:	
PPE:	Work gloves.
Characteristics:	«CE» marking, category I.
CEN standards:	EN 374-1, EN 374-2, EN 374-3, EN 420



SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



BLACK ALUMINUM

Version: 4
Revision date: 09/11/2017

Page 5 of 9
Print date: 09/11/2017

Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.): > 480	Material thickness (mm): 0,35
Eye protection:			
PPE:	Protective goggles against particle impacts.		
Characteristics:	«CE» marking, category II. Eye protector against dust and smoke.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.		
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.		
Skin protection:			
PPE:	Anti-static protective clothing.		
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.		
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5		
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.		
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.		
PPE:	Anti-static safety footwear.		
Characteristics:	«CE» marking, category II.		
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346		
Maintenance:	The footwear should be checked regularly		
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.		

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Powder
Colour: Grey
Odour: Odourless
Odour threshold: N.A./N.A.
pH: N.A./N.A.
Melting point: 660 °C
Boiling Point: 2467 °C
Flash point: 12 °C
Evaporation rate: N.A./N.A.
Inflammability (solid, gas): N.A./N.A.
Lower Explosive Limit: 40 g/cm³
Upper Explosive Limit: N.A./N.A.
Vapour pressure: N.A./N.A.
Vapour density: N.A./N.A.
Relative density: 2,7 g/cm³
Solubility: Insoluble in water and organic solvents
Liposolubility: N.A./N.A.
Hydrosolubility: N.A./N.A.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



BLACK ALUMINUM

Version: 4
Revision date: 09/11/2017

Page 6 of 9
Print date: 09/11/2017

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A.

Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A.

Explosive properties: Fine aluminum in powder may be explosive if disperse into a dust cloud in air in the oresence of sourceof ignition

Oxidizing properties: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Pour point: N.A./N.A.

Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

May react with acids and oxidizing agents or halogenated hydrocarbons

10.2 Chemical stability.

Unstable in contact with:

- Water.

10.3 Possibility of hazardous reactions.

No more information is known

10.4 Conditions to avoid.

In prolonged contact with water can give reactions that release hydrogen

10.5 Incompatible materials.

Avoid the following materials:

Acids, Oxidizing materials and halogenated hydrocarbons.

10.6 Hazardous decomposition products.

No more information is known

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Not conclusive data for classification.

c) serious eye damage/irritation;

Not conclusive data for classification.

d) respiratory or skin sensitisation;

Not conclusive data for classification.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



BLACK ALUMINUM

Version: 4
Revision date: 09/11/2017

Page 7 of 9
Print date: 09/11/2017

e) germ cell mutagenicity;
Not conclusive data for classification.

f) carcinogenicity;
Not conclusive data for classification.

g) reproductive toxicity;
Not conclusive data for classification.

h) STOT-single exposure;
Not conclusive data for classification.

i) STOT-repeated exposure;
Not conclusive data for classification.

j) aspiration hazard;
Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity.

12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potencial.

No information is available regarding the bioaccumulation.

12.4 Mobility in soil.

No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13 DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.
Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



BLACK ALUMINUM

Version: 4
Revision date: 09/11/2017

Page 8 of 9
Print date: 09/11/2017

Land: Transport by road: ADR, Transport by rail: RID.
Transport documentation: Consignment note and written instructions
Sea: Transport by ship: IMDG.
Transport documentation: Bill of lading
Air: Transport by plane: ICAO/IATA.
Transport document: Airway bill.

14.1 UN number.
UN No: UN1309

14.2 UN proper shipping name.
Description:
ADR: UN 1309, ALUMINIUM POWDER, COATED, 4.1, PG II, (E)
IMDG: UN 1309, ALUMINIUM POWDER, COATED, 4.1, PG II
ICAO: UN 1309, ALUMINIUM POWDER, COATED, 4.1, PG II

14.3 Transport hazard class(es).
Class(es): 4.1

14.4 Packing group.
Packing group: II

14.5 Environmental hazards.
Marine pollutant: No

14.6 Special precautions for user.
Labels: 4.1



Hazard number: 40
ADR LQ: 1 kg
IMDG LQ: 1 kg
ICAO LQ: 5 kg

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.
Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-G,S-G
Proceed in accordance with point 6.
IMDG Code segregation group: 15 Powdered metals

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.
The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance.
The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

The product is not affected by Directive 2012/18/EU (SEVESO III).
The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)



BLACK ALUMINUM

Version: 4
Revision date: 09/11/2017

Page 9 of 9
Print date: 09/11/2017

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Classification codes:

Flam. Sol. 1 : Flammable solid, Category 1

Water-react. 2 : Substances and mixtures, which in contact with water, emit flammable gases, Category 2

Sections changed compared with the previous version:

7,10

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CEN: European Committee for Standardization.

DREL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

PPE: Personal protection equipment.

IATA: International Air Transport Association.

ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.